

hangulmath

Hangul jamo as mathematical symbols

Inkyu Park
icpark00@gmail.com

Version 0.9 2026/10/21

訓民正號

훈민정호 — 백성을 가르치는 바른 기호

The Correct Symbols for the Instruction of the People

나랏 수식이 로마자와 희랍자에 머물러 그 수가 넉넉디 아니할쎄, 이런 전차로 어린 수학자가 쓰고저
홀 새 변수가 이셔도 마참내 제 뜨들 시러 퍼디 못할 노미 하니라.

내 이랄 어엿비 너겨 새로 마흔 기호를 맹가노니, 학자마다 수비 니겨 날로 레이텍에 쑤메 편안케
하고저 할 따라미니라.

$$\#\{\neg, \sqcup, \sqcap, \dots, \neg, \neg\} = 19 + 21 = 40$$

병오년(2026) 한글날

Whereas the symbols of our mathematics remain confined to the Roman and Greek letters, and their number is not sufficient, many a humble mathematician, though wishing to write a new variable, has in the end been unable to express his meaning.

Taking pity on them, I have newly made forty symbols, so that every scholar may learn them with ease and use them daily in $\text{\LaTeX}$; and this is all I desire.

$$\#\{\neg, \sqcup, \sqcap, \dots, \neg, \neg\} = 19 + 21 = 40$$

Given on Hangul Day, in the year 2026

Contents

1	Introduction	3
2	Requirements and installation	3
3	Usage	4
3.1	Package options	4
3.2	Using with kotex	4
4	The symbols	5
4.1	Naming rules	5
4.2	Consonants	5
4.3	Double consonants	6
4.4	Vowels and compound vowels	6
5	More examples	6
5.1	Vowels as brackets	6
5.2	Consonants as function names	8
5.3	Π the Hamiltonian, Ξ the Lagrangian	9
5.4	ㅈ as a superscript mark	10
5.5	ㅊ , ㅌ , ㅍ , ㅍ as arrows	11
5.6	Consonants as element symbols	12
5.7	Operators	13
5.8	In running text	13
6	Using other fonts	13
7	Caveats	14
8	Korean summary (한국어 요약)	14
9	License	14
10	Change history	14

1 Introduction

Mathematical notation draws almost entirely on the Latin and Greek alphabets, and in a long paper one easily runs out of distinct letters. The Korean alphabet, Hangul, offers a clean supply of new symbols: its letters (*jamo*) are built from simple geometric strokes, are visually distinct from Latin and Greek, and each has a well-established name.

The `hangulmath` package makes the 40 jamo of modern Hangul available in mathematics: 14 basic consonants, 5 double consonants, 10 basic vowels and 11 compound vowels. Each symbol has a command named after the letter, so $\mathfrak{A}$ is `\giyeok`, much as α is `\alpha`. Consonants also have a four-letter alias that is easy to remember (`\giug`).

$$\mathfrak{A}(x) = \sum_k \mathfrak{L}_k x^k, \quad \square^2 \vec{A} = -\mu_0 \vec{J}, \quad \mathfrak{A}|\psi\rangle\langle\phi| = \int \psi^* \phi dx.$$

The symbols are taken from a bundled subset of the Noto Sans CJK KR typeface, so no Korean font needs to be installed.

2 Requirements and installation

`hangulmath` works with **pdfLaTeX**, **XeLaTeX** and **LuaLaTeX**, and with `latex` followed by `dvips` or `dvipdfmx`. It needs a LaTeX kernel from 2022 or later.

- With **XeLaTeX** and **LuaLaTeX** the symbols come from the bundled OpenType fonts, loaded with `fontspec`.
- With **pdfLaTeX** (and the DVI route) they come from the same fonts converted to Type 1 (`.pfb` with `.tfm` metrics). The outlines and advance widths are identical, so the output is the same as with XeLaTeX. The symbols are given Unicode names, and the package switches on `\pdfgentounicode`, so they can be copied and searched in the PDF.

The option `font` and the command `\hangulmathfont` load another OpenType font and therefore need XeLaTeX or LuaLaTeX; under pdfLaTeX they are ignored with a warning.

TeX Live and MiKTeX. Once the package is distributed via CTAN it is installed with the usual package manager (`tlmgr install hangulmath`, or automatically by MiKTeX).

Manual installation. The package consists of these files:

files	texmf directory	needed for
<code>.sty</code> <code>.def</code>	<code>tex/latex/hangulmath/</code>	all engines
<code>.otf</code>	<code>fonts/opentype/public/hangulmath/</code>	XeLaTeX, LuaLaTeX
<code>.pfb</code>	<code>fonts/type1/public/hangulmath/</code>	pdfLaTeX, DVI
<code>.tfm</code>	<code>fonts/tfm/public/hangulmath/</code>	pdfLaTeX, DVI
<code>.map</code>	<code>fonts/map/dvips/hangulmath/</code>	DVI drivers

The font is `hangulmath-sans` in each format. To use the package without installing it (for example on Overleaf), copy these files into the directory of your document:

- pdfLaTeX (4 files): `hangulmath.sty`, `hangulmath-metrics.def`, `hangulmath-sans.pfb`, `hangulmath-sans.tfm`;

- XeLaTeX or LuaLaTeX (3 files): `hangulmath.sty`, `hangulmath-metrics.def`, `hangulmath-sans.otf`.

In a local `texmf` tree, use the directories shown, then run `mktexlsr` and

`updmap-user --enable Map=hangulmath.map`

Under pdfLaTeX the package registers the font map itself (`\pdfmapline`), so the fonts work even without `updmap`. The DVI drivers need the enabled map, or it can be given on the command line, e.g. `dvips -u +hangulmath.map`.

Overleaf. Upload the eight files of the first four rows into your project. The default compiler, pdfLaTeX, works; so do XeLaTeX and LuaLaTeX.

3 Usage

`\usepackage{hangulmath}`

...

`$\giyeok + \nieun = \digeut$` or, with aliases, `$\giug + \niun = \diud$`

Every symbol command works in math mode and also in running text (it uses `\ensuremath`). The symbols are ordinary math symbols (`\mathord`): they take sub- and superscripts and scale correctly in script styles. They are always set upright, whatever the surrounding text font.

`$\giug_{\ah}(x)$`, `$\niun^{\ih j}$`, `$X\giug x\niun$` $\neg_l(x)$, $\sqcup^j$, $X\neg x\sqcup$

3.1 Package options

option	meaning
<code>font=\langle font \rangle</code>	Font for the symbols, given by name or file name (XeLaTeX and LuaLaTeX only). Default: the bundled <code>hangulmath-sans.otf</code> (HangulMath Sans DemiLight).
<code>metrics=\langle file \rangle</code>	Name (without <code>.def</code>) of the metrics file that describes the glyphs of <code>font</code> . Default: <code>hangulmath-metrics</code> , which matches the bundled font. See Section 6.
<code>scale=\langle number \rangle</code>	Scale factor for the symbol font. Default: taken from the metrics file (about 1.24 for the bundled font).
<code>sidebearing=\langle em \rangle</code>	Space, in em, added to the left and right of each glyph. Default: 0.06.

If a requested font is not installed, `hangulmath` issues a warning and uses the bundled font instead, so that documents always compile.

3.2 Using with kotex

`hangulmath` works together with the Korean typesetting package `kotex` (`xetexko` or `luatexko`), loaded before or after it. `kotex` normally sends every Hangul character to its own Korean

text font; `hangulmath` switches this off locally inside its symbols, so they always come from the symbol font, with the same size and alignment as without `kotex`.

`kotex` already uses the command name `\rieul` (as a josa command), so `hangulmath` leaves that name untouched and prints a warning. Write $\rceil$ as `\liul` instead.

\hangulsym. More generally, if any command name is already taken by another package, `hangulmath` does not overwrite it but warns, naming the alternatives. Every symbol can always be reached by name:

`$\hangulsym{rieul} = \hangulsym{liul} = \liul$` $\rceil = \rceil = \rceil$

4 The symbols

4.1 Naming rules

- **Official names** follow the Revised Romanization of Korean: `\giyeok`, `\nieun`, ..., `\ssanggiyeok`.
- **Consonant aliases** have four letters: the consonant, `iu`, and the consonant again, imitating the shape of the Korean letter names (기역 $\rightarrow$ `\giug`, 니은 $\rightarrow$ `\niun`). Their first letters are all different, so the first letter alone identifies the consonant. Two adjustments are needed: $\circ$ has no initial sound and is `\iung`; $\ddot{\text{z}}$ is written with `c` to keep four letters, `\ciuc`. $\rceil$ uses `l`, its sound at the end of a syllable.
- **Double consonants** double the first letter of the alias: `\ggiug`, `\ddiud`, `\bbiub`, `\ssius`, `\jjiuj`.
- **Vowels** are written as pronounced, followed by `h`: `\ah`, `\eoh`, `\ih`. The trailing `h` avoids clashes with existing commands such as `\a`, `\o`, `\u` and `\i`. In compound vowels the glide *w* is written `u` (`\uah` for ㅜㅏ). ㅟ is `\euih` (ㅡㅗㅟ) to distinguish it from ㅜㅣ , `\uih`.

4.2 Consonants

	official	alias	Unicode		official	alias	Unicode
ㄱ	<code>\giyeok</code>	<code>\giug</code>	U+3131	ㅇ	<code>\ieung</code>	<code>\iung</code>	U+3147
ㄴ	<code>\nieun</code>	<code>\niun</code>	U+3134	ㄷ	<code>\jieut</code>	<code>\jiuj</code>	U+3148
ㄷ	<code>\digeut</code>	<code>\diud</code>	U+3137	ㄸ	<code>\chieut</code>	<code>\ciuc</code>	U+314A
ㄹ	<code>\rieul</code>	<code>\liul</code>	U+3139	ㄱ	<code>\kieuk</code>	<code>\kiuk</code>	U+314B
ㅁ	<code>\mieum</code>	<code>\mium</code>	U+3141	ㅌ	<code>\tieut</code>	<code>\tiut</code>	U+314C
ㅂ	<code>\bieup</code>	<code>\biub</code>	U+3142	ㅍ	<code>\pieup</code>	<code>\piup</code>	U+314D
ㅅ	<code>\siot</code>	<code>\sius</code>	U+3145	ㅎ	<code>\hieut</code>	<code>\hiuh</code>	U+314E

4.3 Double consonants

	official	alias	Unicode
ㄱ	\ssanggiyeok	\ggiug	U+3132
ㅋ	\ssangdigeut	\ddiud	U+3138
ㆁ	\ssangbieup	\bbiub	U+3143
ㄴ	\ssangsiot	\ssius	U+3146
ㄹ	\ssangjieut	\jjuij	U+3149

4.4 Vowels and compound vowels

	command	Unicode
𐤀	\ah	U+314F
𐤁	\yah	U+3151
𐤂	\eoh	U+3153
𐤃	\yeoh	U+3155
𐤄	\oh	U+3157
𐤅	\yoh	U+315B
𐤆	\uh	U+315C
𐤇	\yuh	U+3160
𐤈	\euh	U+3161
𐤉	\ih	U+3163

	command	Unicode
ⱥ	\aeh	U+3150
ⱦ	\yaeh	U+3152
Ⱨ	\eh	U+3154
ⱨ	\yeh	U+3156
Ⱪ	\uah	U+3158
ⱪ	\uaeh	U+3159
ⱬ	\oeh	U+315A
Ɑ	\ueoh	U+315D
Ɱ	\ueh	U+315E
Ɐ	\uih	U+315F
Ɒ	\euih	U+3162

5 More examples

Each example below shows the $\text{\LaTeX}$ input (shaded, labelled **LaTeX**) directly above its typeset result (labelled **Output**). Unless an example says otherwise, the input is math and is set in display style. The notations are suggestions, not standards; define them in your text before using them.

5.1 Vowels as brackets

The vowels $\lrcorner$ and $\llcorner$ are mirror images, with a stroke pointing outwards like the angle brackets $\langle \rangle$. They give a Dirac notation in which a bra is $\lrcorner\psi$ and a ket is $|\phi\llcorner$. The vowels with two strokes, $\lrcorner$ and $\llcorner$, give double brackets $\langle\langle \rangle\rangle$, as used for operators in Liouville space. Reversed pairs, with the strokes pointing inwards, make further kinds of bracket. Macros such as `\newcommand\ket[1]{| $\#1$ \llcorner}` shorten the input.

$$\int \psi^*(x) \phi(x) dx$$

Output

$$\langle \psi | \phi \rangle = \int \psi^*(x) \phi(x) dx$$

$$|\psi\rangle_{\phi} = |\psi\rangle_{\psi}^*$$

Output

$$\vdash \phi \mid \psi \vdash = \vdash \psi \mid \phi \vdash^*$$

LaTeX	<code>\psi\ah = \sum_n c_n\, n\ah, \quad c_n = \eoh n \psi\ah</code>
Output	$ \psi\rangle = \sum_n c_n n\rangle, \quad c_n = \langle n \psi\rangle$
LaTeX	<code>\sum_n n\ah\eoh n = \mathbf{1}</code>
Output	$\sum_n n\rangle\langle n = \mathbf{1}$
LaTeX	<code>\eoh A\ah = \eoh\psi A \psi\ah, \quad (\Delta A)^2 = \eoh A^2\ah - \eoh A\ah^2</code>
Output	$\langle A\rangle = \langle\psi A \psi\rangle, \quad (\Delta A)^2 = \langle A^2\rangle - \langle A\rangle^2$
LaTeX	<code>\eoh x p\ah = \frac{1}{\sqrt{2\pi\hbar}}\,e^{\mathrm{i}p x/\hbar}</code>
Output	$\langle x p\rangle = \frac{1}{\sqrt{2\pi\hbar}} e^{\mathrm{i}p x/\hbar}$
LaTeX	<code>\eoh x x'\ah = \delta(x - x')</code>
Output	$\langle x x'\rangle = \delta(x - x')$
LaTeX	<code>\yeoh A B\yah = \operatorname{Tr}(A^\dagger B)</code>
Output	$\langle A B\rangle = \mathrm{Tr}(A^\dagger B)$
LaTeX	<code>\frac{d}{dt} \rho\yah = \mathcal{L}\, \rho\yah</code>
Output	$\frac{d}{dt} \rho\rangle = \mathcal{L} \rho\rangle$
LaTeX	<code>\eoh A(t)\ah = \yeoh A e^{\mathcal{L}t} \rho_0\yah</code>
Output	$\langle A(t)\rangle = \langle A e^{\mathcal{L}t} \rho_0\rangle$
LaTeX	<code>\ah A, B\eah = AB + BA, \quad \ah\psi(x), \psi^\dagger(y)\eah = \delta(x - y)</code>
Output	$\langle A, B\rangle = AB + BA, \quad \langle\psi(x), \psi^\dagger(y)\rangle = \delta(x - y)$
LaTeX	<code>\yah A B\yeoh = \int_0^1 \operatorname{Tr}(A^\dagger\rho^s B\rho^{1-s})\,ds</code>
Output	$\langle A B\rangle = \int_0^1 \mathrm{Tr}(A^\dagger \rho^s B \rho^{1-s}) \, ds$
LaTeX	<code>\aeh P, Q\eah = -(-1)^{(p-1)(q-1)}\, \aeh Q, P\eah, \quad \aeh\pi, \pi\eah = 0</code>
Output	$\langle\!\langle P, Q\rangle\!\rangle = -(-1)^{(p-1)(q-1)} \langle\!\langle Q, P\rangle\!\rangle, \quad \langle\!\langle \pi, \pi\rangle\!\rangle = 0$

5.2 Consonants as function names

Followed by an argument, a consonant reads naturally as the name of a function. Some shapes suggest a meaning: $\neg$ looks like a mirrored Γ , and makes a good name for the reciprocal gamma function; $\square$ is a box, the rectangle function; $\blacktriangle$ is a tent, the triangle function; and $\bigcirc$ is a disc, the circle function of optics.

LaTeX	<code>\giug(x), \niun(x), \diud(x), \liul(x), \mium(x), \biub(x), \sius(x)</code>
Output	$\neg(x), \sqsubset(x), \sqsubset(x), \sqsupset(x), \square(x), \boxplus(x), \blacktriangle(x)$
LaTeX	<code>\iung(x), \jiuj(x), \ciuc(x), \kiuk(x), \tiut(x), \piup(x), \hiuh(x)</code>
Output	$\bigcirc(x), \bowtie(x), \pitchfork(x), \supset(x), \Xi(x), \Pi(x), \textcircled{x}$
LaTeX	<code>\ggiug(x), \ddiud(x), \bbiub(x), \ssius(x), \jjjuj(x)</code>
Output	$\neg(x), \boxtimes(x), \boxtimes(x), \blacklozenge(x), \blacklozenge(x)$
LaTeX	<code>\giug(z) = \frac{1}{\Gamma(z)}, \quad \quad \quad \neg(z) \neg(1-z) = \frac{\sin \pi z}{\pi}</code>
Output	$\neg(z) = \frac{1}{\Gamma(z)}, \quad \quad \quad \neg(z) \neg(1-z) = \frac{\sin \pi z}{\pi}$
LaTeX	<code>\giug(z) = z \cdot e^{\gamma z} \prod_{n=1}^{\infty} \left(1 + \frac{z}{n}\right) e^{-z/n}</code>
Output	$\neg(z) = z e^{\gamma z} \prod_{n=1}^{\infty} \left(1 + \frac{z}{n}\right) e^{-z/n}$
LaTeX	<code>\mium(x) = \begin{cases} 1, & x < \frac{1}{2} \\ 0, & x > \frac{1}{2} \end{cases}</code>
Output	$\square(x) = \begin{cases} 1, & x < \frac{1}{2} \\ 0, & x > \frac{1}{2} \end{cases}$
LaTeX	<code>\sius(x) = \max(1 - x , 0)</code>
Output	$\blacktriangle(x) = \max(1 - x , 0)$
LaTeX	<code>\mium * \mium = \sius, \quad \quad \quad \hat{\neg}(k) = \operatorname{sinc} \frac{k}{2}</code>
Output	$\square * \square = \blacktriangle, \quad \quad \quad \hat{\neg}(k) = \operatorname{sinc} \frac{k}{2}$
LaTeX	<code>\hat{\sius}(k) = \operatorname{sinc}^2 \frac{k}{2}</code>
Output	$\hat{\blacktriangle}(k) = \operatorname{sinc}^2 \frac{k}{2}$
LaTeX	<code>\iung(r) = \begin{cases} 1, & r < 1 \\ 0, & r > 1 \end{cases}</code>
Output	$\bigcirc(r) = \begin{cases} 1, & r < 1 \\ 0, & r > 1 \end{cases}$

LaTeX `\hat{\iung}(\rho) = \frac{J_1(2\pi\rho)}{\rho}`

Output $\hat{\mathcal{O}}(\rho) = \frac{J_1(2\pi\rho)}{\rho}$

5.3 $\mathbb{H}$ the Hamiltonian, Ξ the Lagrangian

With its two horizontal bars and two posts, $\mathbb{H}$ is a sturdy letter for the Hamiltonian; Ξ is the first consonant of 라그랑지안.

LaTeX `\piup\,,|\psi\ah = E\,,|\psi\ah`

Output $\mathbb{H}|\psi\rangle = E|\psi\rangle$

LaTeX `i\hbar\,,\frac{\partial}{\partial t}|\psi(t)\ah = \piup\,,|\psi(t)\ah`

Output $i\hbar \frac{\partial}{\partial t}|\psi(t)\rangle = \mathbb{H}|\psi(t)\rangle$

LaTeX `\piup = \frac{p^2}{2m} + V(x)\,, \quad E_n = \langle n|\piup|n\ah`

Output $\mathbb{H} = \frac{p^2}{2m} + V(x), \quad E_n = \langle n|\mathbb{H}|n\rangle$

LaTeX `\frac{dA}{dt} = \frac{i}{\hbar}[\piup, A] + \frac{\partial A}{\partial t}`

Output $\frac{dA}{dt} = \frac{i}{\hbar}[\mathbb{H}, A] + \frac{\partial A}{\partial t}$

LaTeX `\frac{df}{dt} = \{f, \piup\}`

Output $\frac{df}{dt} = \{f, \mathbb{H}\}$

LaTeX `Z = \operatorname{Tr} e^{-\beta\piup}\,, \quad \rho = \frac{e^{-\beta\piup}}{Z}`

Output $Z = \operatorname{Tr} e^{-\beta\mathbb{H}}, \quad \rho = \frac{e^{-\beta\mathbb{H}}}{Z}$

LaTeX `F = -\frac{1}{\beta}\ln Z`

Output $F = -\frac{1}{\beta} \ln Z$

LaTeX `\langle q_f|e^{-i\piup t/\hbar}|q_i\ah = \int \mathcal{D}q\; e^{iS[q]/\hbar}`

Output $\langle q_f|e^{-i\mathbb{H}t/\hbar}|q_i\rangle = \int \mathcal{D}q e^{iS[q]/\hbar}$

LaTeX `S[q] = \int \mathbb{L}\,dt`

Output $S[q] = \int \Xi dt$

LaTeX	<code>\frac{d}{dt}\frac{\partial\liul}{\partial\dot q}=\frac{\partial\liul}{\partial q}</code>
Output	$\frac{d}{dt}\frac{\partial\Xi}{\partial\dot q} = \frac{\partial\Xi}{\partial q}$
LaTeX	<code>\piup = p\,\dot q - \liul</code>
Output	$\Pi = p\dot q - \Xi$
LaTeX	<code>\dot q = \frac{\partial\piup}{\partial p}</code>
Output	$\dot q = \frac{\partial\Pi}{\partial p}$
LaTeX	<code>\dot p = -\frac{\partial\piup}{\partial q}</code>
Output	$\dot p = -\frac{\partial\Pi}{\partial q}$
LaTeX	<code>\liul = -\tfrac{1}{4} F_{\mu\nu}F^{\mu\nu} + \bar\psi\gamma^\mu D_\mu\psi</code>
Output	$\Xi = -\frac{1}{4}F_{\mu\nu}F^{\mu\nu} + \bar\psi(i\gamma^\mu D_\mu - m)\psi$

5.4 大 as a superscript mark

Set as a superscript, 大 joins the prime, the asterisk and the dagger as a mark for a new kind of conjugate, dual or distinguished point.

LaTeX	<code>A',\quad A^*,\quad A^\dagger,\quad A^{\text{ciuc}}</code>
Output	$A', \quad A^*, \quad A^\dagger, \quad A^\text{大}$
LaTeX	<code>(AB)^{\text{ciuc}} = B^{\text{ciuc}}A^{\text{ciuc}}, \quad (A^{\text{ciuc}})^{\text{ciuc}} = A</code>
Output	$(AB)^\text{大} = B^\text{大}A^\text{大}, \quad (A^\text{大})^\text{大} = A$
LaTeX	<code>\eoh\psi A\phi\ah = \eoh A^{\text{ciuc}}\psi \phi\ah</code>
Output	$\langle\psi A\phi\rangle = \langle A^\text{大}\psi \phi\rangle$
LaTeX	<code>f^{\text{ciuc}}(y) = \sup_x\bigl(xy - f(x)\bigr)</code>
Output	$f^\text{大}(y) = \sup_x(xy - f(x))$
LaTeX	<code>f^{\text{ciuc}\text{ciuc}} = f \quad \text{\textit{f convex}}</code>
Output	$f^{\text{大}\text{大}} = f \quad (f \text{ convex})$
LaTeX	<code>\piup(q,p) = \liul^{\text{ciuc}} = \sup_{\dot q}\bigl(p\,\dot q - \liul(q,\dot q)\bigr)</code>
Output	$\Pi(q,p) = \Xi^\text{大} = \sup_{\dot q}(p\dot q - \Xi(q,\dot q))$

LaTeX `x^{\ciuc} = \operatorname*{arg\,min}_x f(x), \quad \qquad \nabla f(x^{\ciuc}) = 0`

Output $x^{\star} = \arg \min_x f(x), \quad \nabla f(x^{\star}) = 0$

LaTeX `T^{\ciuc}, \ p^{\ciuc}, \ V^{\ciuc}`

Output $T^{\star}, p^{\star}, V^{\star}$

5.5 $\perp$, $\ll$, $\top$, Π as arrows

The stroke of $\perp$ points up and that of $\top$ points down; $\ll$ and Π have two strokes. They serve as arrows: spins up and down, the electrons of an oxygen atom in its orbitals, gas evolved and precipitate formed, monotone limits, and Knuth's arrow notation. Wrap them in `\mathrel` or `\mathbin` where they act as relations or operations, so that they get the right spacing.

LaTeX `\sigma_z|\oh\ah = +|\oh\ah, \quad \quad \sigma_z|\uh\ah = -|\uh\ah`

Output $\sigma_z|\perp\rangle = +|\perp\rangle, \quad \sigma_z|\top\rangle = -|\top\rangle$

LaTeX `S_+|\uh\ah = \hbar\,|\oh\ah`

Output $S_+|\top\rangle = \hbar|\perp\rangle$

LaTeX `|\psi^-\ah = \frac{1}{\sqrt{2}}\bigl(|\oh\uh\ah - |\uh\oh\ah\bigr)`

Output $|\psi^-\rangle = \frac{1}{\sqrt{2}}(|\perp\top\rangle - |\top\perp\rangle)$

LaTeX `|\yoh\ah = |\oh\oh\ah, \quad |\yuh\ah = |\uh\uh\ah`

Output $|\ll\rangle = |\perp\perp\rangle, \quad |\Pi\rangle = |\top\top\rangle$

LaTeX `1s\boxed{\oh\uh}\; \; 2s\boxed{\oh\uh}\; \; 2p\boxed{\oh\uh}\boxed{\oh}\boxed{\oh}`

Output $1s\boxed{\perp\top} \quad 2s\boxed{\perp\top} \quad 2p\boxed{\perp\top}\boxed{\perp}\boxed{\perp}$

LaTeX `\mathrm{CaCO_3 + 2HCl \to CaCl_2 + H_2O + CO_2}\ah`

Output $\mathrm{CaCO_3 + 2HCl \rightarrow CaCl_2 + H_2O + CO_2} \perp$

LaTeX `\mathrm{Ag^{+}} + \mathrm{Cl^{-}} \to \mathrm{AgCl}\ah`

Output $\mathrm{Ag^{+} + Cl^{-} \rightarrow AgCl} \top$

LaTeX `\mathrm{Ba^{2+}} + \mathrm{SO_4^{2-}} \to \mathrm{BaSO_4}\ah`

Output $\mathrm{Ba^{2+} + SO_4^{2-} \rightarrow BaSO_4} \top$

LaTeX `x \mathrel{\uh} 0 \quad \quad (x \downarrow 0)`

Output $x \top 0 \quad (x \downarrow 0)$

LaTeX `f_n \mathrel{\mathbin{\lrcorner}} f \implies \int f_n d\mu \mathrel{\mathbin{\lrcorner}} \int f d\mu`

Output $f_n \mathbin{\lrcorner} f \implies \int f_n d\mu \mathbin{\lrcorner} \int f d\mu$

LaTeX `a \mathbin{\mathbb{A}} b = a^b, \quad 2 \mathbb{A} 4 = 2^{2^2} = 65536`

Output $a \mathbin{\mathbb{A}} b = a^b, \quad 2 \mathbb{A} 4 = 2^{2^2} = 65536$

5.6 Consonants as element symbols

With pre-scripts for mass and atomic numbers, consonants become the symbols of imaginary elements, and enter formulas, equations and equilibrium constants like real ones.

LaTeX `{\scriptsize 298}_{120}\giug \to {\scriptsize 294}_{118}\niun + {\scriptsize 4}_2\mathrm{He}`

Output ${}^{298}_{120}\mathfrak{G} \rightarrow {}^{294}_{118}\mathfrak{N} + {}^4_2\mathrm{He}$

LaTeX `{\scriptsize 14}_6\ciuc \to {\scriptsize 14}_7\diud + e^- + \bar{\nu}_e`

Output ${}^{14}_6\mathfrak{C} \rightarrow {}^{14}_7\mathfrak{D} + e^- + \bar{\nu}_e$

LaTeX `2\,\giug_2 + \iung_2 \rightleftharpoons 2\,\giug_2\iung`

Output $2\mathfrak{G}_2 + \mathfrak{I} \rightleftharpoons 2\mathfrak{G}_2\mathfrak{I}$

LaTeX `K = \frac{[\giug_2\iung]^2}{[\giug_2]^2[\iung_2]}`

Output $K = \frac{[\mathfrak{G}_2\mathfrak{I}]^2}{[\mathfrak{G}_2]^2[\mathfrak{I}_2]}$

LaTeX `\ssius^{2+} + 2\,\diud^- \to \ssius\diud_2\,\uh`

Output $\mathfrak{S}^{2+} + 2\mathfrak{D}^- \rightarrow \mathfrak{S}\mathfrak{D}_2\mathfrak{T}$

LaTeX `\biub\liul_3 + 3\,\mathrm{H}_{20} \to \biub(\mathrm{OH})_3 + 3\,\mathrm{H}\liul`

Output $\mathfrak{B}\mathfrak{L}_3 + 3\mathrm{H}_2\mathrm{O} \rightarrow \mathfrak{B}(\mathrm{OH})_3 + 3\mathrm{H}\mathfrak{L}$

LaTeX `\mathrm{C}_{6\mathrm{H}_{12}\mathrm{O}_6} + 6\,\iung_2 \to 6\,\mathrm{C}\iung_2 + 6\,\mathrm{H}_2\iung`

Output $\mathrm{C}_6\mathrm{H}_{12}\mathrm{O}_6 + 6\mathfrak{I}_2 \rightarrow 6\mathrm{C}\mathfrak{I}_2 + 6\mathrm{H}_2\mathfrak{I}$

5.7 Operators

The shape of $\Box$ suggests the d'Alembertian (box) operator. A symbol can also take limits like $\lim$, using the standard L^AT_EX commands `\mathop` and `\limits`; no extra command is needed.

LaTeX `\mum^2 \equiv \nabla^2 - \frac{1}{c^2} \frac{\partial^2}{\partial t^2}`

Output $\Box^2 \equiv \nabla^2 - \frac{1}{c^2} \frac{\partial^2}{\partial t^2}$

LaTeX `\mum^2 A^\mu = -\mu_0 J^\mu, \quad \Box^2 A^\mu = -\mu_0 J^\mu, \quad (\Box^2 - m^2) \phi = 0`

Output $\Box^2 A^\mu = -\mu_0 J^\mu, \quad (\Box^2 - m^2) \phi = 0$

LaTeX `\mathop{\lim}_{n \rightarrow \infty} \Bigl(1 + \frac{1}{n}\Bigr)^n = e`

Output $\lim_{n \rightarrow \infty} \left(1 + \frac{1}{n}\right)^n = e$

LaTeX `{_2\biub_1(a,b;c;z) = \sum_{n \geq 0} \frac{(a)_n (b)_n}{(c)_n n!} z^n`

Output ${}_2\mathbf{H}_1(a, b; c; z) = \sum_{n \geq 0} \frac{(a)_n (b)_n}{(c)_n n!} z^n$

5.8 In running text

The symbol commands also work outside math mode. This input is text, not math.

LaTeX `Spin up is  $\uparrow$ , spin down  $\downarrow$ ; also in plain text:  $\uparrow$  and  $\downarrow$ .`

Output Spin up is $\uparrow$, spin down $\downarrow$; also in plain text: $\uparrow$ and $\downarrow$.

6 Using other fonts

This section applies to XeLaTeX and LuaLaTeX; pdfLaTeX always uses the bundled font. Hangul compatibility jamo are drawn small and high in the em square of most Korean fonts, with large side bearings. `hangulmath` therefore scales all glyphs by a common factor, lowers them by a common amount so that consonants sit on the baseline, and trims each glyph to its ink. These values depend on the font and are stored in a metrics file.

To use another font, generate a metrics file with the Python script `hangulmath-metrics.py` (Python 3.10+, `pip install fonttools`):

```
python3 hangulmath-metrics.py "Nanum Gothic" -o nanum.def
```

and load it together with the font:

```
\usepackage[font={Nanum Gothic}, metrics=nanum]{hangulmath}
```

`\hangulmathfont{font}` changes the font later in the preamble.

7 Caveats

- **Look-alikes.** — resembles a minus sign and $|$ a vertical bar. Use them with care, and say in the text which letter you mean.
- **Submissions.** Since version 0.8 the package works with pdfLaTeX, so documents using it can be compiled by arXiv and by the usual journal systems. Include the font files (`.pfb`, `.tfm`) with your sources if the server's TeX installation does not have `hangulmath` yet.
- **Name clashes.** If another package defines a command with the same name as a symbol, the other package wins and `hangulmath` warns; use the alias or `\hangulsym` (Section 3.2).
- **Searchability.** The symbols are real Unicode characters in the PDF, so they can be copied and searched.

8 Korean summary (한국어 요약)

`hangulmath`는 현대 한글 자모 40자(기본 자음 14, 쌍자음 5, 기본 모음 10, 복모음 11)를 수식 기호로 쓸 수 있게 하는 패키지입니다. pdfLaTeX, XeLaTeX, LuaLaTeX에서 모두 동작하며, 기호용 고딕체 글꼴이 OpenType과 Type 1 두 형식으로 함께 들어 있어 따로 한글 글꼴을 설치할 필요가 없습니다. 다른 글꼴을 기호로 쓰는 `font` 옵션은 XeLaTeX와 LuaLaTeX에서만 쓸 수 있습니다.

명령어는 로마자 표기법에 따른 공식 이름(`\giyeok`)과 외우기 쉬운 네 글자 약어(`\giug`)가 있습니다. 약어는 자음, `iu`, 자음의 순서이며, 쌍자음은 첫 글자를 두 번 씁니다(`\ggiug`). 모음은 소리 나는 대로 쓰고 끝에 `h`를 붙입니다(`\ah`, `\uah`).

모음은 괄호로도 쓸 수 있습니다. 예컨대 디랙 표기 $\langle\psi|\phi\rangle$ 를 $\langle\psi|\phi|$ 로 씁니다. 5절에 예제가 더 있습니다.

9 License

Copyright © 2026 Inkyu Park.

Source code and issue tracker: <https://github.com/krunyx/hangulmath>.

The package files may be distributed and/or modified under the conditions of the L^AT_EX Project Public License, version 1.3c or (at your option) any later version.

The bundled font `hangulmath-sans.otf` is a modified (subset and renamed) version of Noto Sans CJK KR DemiLight, copyright 2014–2021 Adobe, and is distributed under the SIL Open Font License 1.1; see `OFL.txt`. It is rebuilt with `hangulmath-fonts.py`. Its Type 1 version (`hangulmath-sans.pfb`, `.tfm`) and `hangulmath.map` are made from it with `hangulmath-type1.py` and are under the same license.

10 Change history

v0.9 (2026/10/21) The operator commands `\hangulsum`, `\hangulint`, `\hangullim` and `\hangulopscale` have been removed, together with the lighter operator font, the option `opfont` and `\hangulmathopfont`. The package now consists of a single font, so four

files are enough under pdfLaTeX and three under XeLaTeX. A symbol can still be used with limits through standard L^AT_EX: `\mathop{\liul}\limits_{x\to\infty}`. The option `opfont` is accepted with a warning so that old documents still compile.

- v0.8 (2026/10/21)** Works with **pdfLaTeX** and with `latex + dvips/dvipdfmx`: the bundled fonts are also shipped as Type 1 fonts with TFM metrics and a map file, built by the new script `hangulmath-type1.py`. The output matches XeLaTeX, and the symbols can be copied from the PDF. Under pdfLaTeX the options `font` and `opfont` are ignored with a warning.
- v0.7 (2026/10/15)** Works with `kotex` (`xetexko` and `luatexko`) in either loading order: the symbols no longer fall into `kotex`'s Korean text font. Command names already defined by another package (such as `kotex`'s `\rieul`) are left alone with a warning instead of causing an error. New command `\hangulsym{<name>}`. New one-page example `hangulmath-minimal.tex`.
- v0.6 (2026/10/11)** Documentation: Section 5 greatly expanded, with each example shown as L^AT_EX input and typeset output: vowels as brackets, consonants as function names, Π as the Hamiltonian, ㅈ as a superscript mark, $\perp$ and $\top$ as arrows, consonants as element symbols. No change to the package code. The preface (Korean and English) rewritten as a closer parody of the Hunminjeongeum; the document preamble offers commented-out lines for choosing another Korean font.
- v0.5 (2026/10/10)** First public release.